## CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL

## FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

## LISTING SERVICE

**LISTING No.** 4075-0035:110 Page 1 of 1

CATEGORY: Glazing/Window Assemblies

LISTING: O'Keeffe's Inc., \*325 Newhall Street, San Francisco, CA 94124-1432

Contact: Kevin Turner (415) 822-4222 Fax (415) 822-5222\*

**DESIGN**: Model "SUPERLITE II XL" glazing material. Refer to listee's data sheet for detailed product

description and operational considerations.

**RATING**: 60 minutes

Nominal 1" in thickness

**INSTALLATION**: In accordance with listee's printed installation instructions, applicable codes and ordinances

and in a manner acceptable to the authority having jurisdiction.

**MARKING**: Listee's name, model number, classification and Warnock Hersey label.

APPROVAL: Listed as 60-minute fire-rated glazing material for use in wood/wood composite or steel fire

doors, steel frames and aluminum frames for sidelights/transom lights/borrowed lights and

door vision panels.

Opening dimensions

Max. Allowable Clear View Area4952 in²2050 in²Max. Allowable Clear View Width106.5"124.25"Max. Allowable Clear View Height106.5"124.25"Minimum Stop Depth5/8"5/8"

NOTE: Allowances:

1. Patterns, Opaque, Tints

- 2. 3/16" high x 1-1/2" wide x 3" long calcium silicate or hardwood setting blocks must be used at quarter points under the bottom edges; and 1/8" thick x 5/8" wide, closed cell foam glazing tape is required on all edges (on both faces).
- 3. Exterior glazing composed of an additional laminate glazing layer with PVB acceptable, including an additional glazing panel.

\*Rev. 06-05-2002



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: JUNE 6, 2003 Listing Expires June 30, 2004

Authorized By: **DIANE K. AREND**, Senior Deputy

Program Manager